

# Industrial Printer 2ST - SATO GY412T

## Adding Another Dimension to Thermal Printing

A direct thermal printer that simultaneously prints on both sides of a label; the printer has 2 thermal print heads. The thermal label media is coated on both sides using thermal technology. The SATO GY412T is great for a wide variety of application: Transportation & logistics, e-commerce forms, shipping labels, financial, and more.



### FEATURES

The SATO GY412T is great for a wide variety of application:

- Transportation & Logistics
- E-Commerce Forms
- Shipping Labels
- Financial
- And More

Liner Eliminator:

- Environmentally Friendly

Operational Benefits:

- Reduce the risk of mismatching packing slip

Lower Cost:

- Eliminates the need for additional printers



# Industrial Printer 2ST - SATO GY412T

## Adding Another Dimension to Thermal Printing

<b>MODEL</b>		<b>SATO GY412T</b>
<b>PRINT SPECIFICATIONS</b>		
Print Method		Direct Thermal
Print Resolution		305 dpi (12 dots/mm)
Print Speed		Up to 10 ips (25 mm/sec)
Max. Print Area		4.09" (104 mm) W x 11.8" (300 mm) L
<b>MEDIA SPECIFICATIONS</b>		
Sensor Type		Reflective Sensor (for use with pre-printed marks) See-Through Sensor (for die-cut labels with gap)
Media Type		Fanfold
Media Size	Width	1.97" (50 mm) - 5.16" (132 mm)
	Length	1.18" (30 mm) - 11.8" (300 mm)
	Thickness	0.004" - 0.013" (0.1 mm - 0.32 mm)
<b>FONT / SYMBOLOGIES</b>		
Font		OCR-A, OCR-B, X20, X21, X22, X23, X24, CG Times, CG Triumvirate
Barcode Symbologies	Linear	UPC-A/E, UCC/EAN-128, Interleaved 2 of 5, CODE 39, CODE 128, EAN-8/13, CODE 93, RSS-14, POSTNET, NW-7, Matrix 2 of 5, MSI, Bookland
	2-Dimensional	Data Matrix, PDF417, Macro PDF, Maxicode, Micro PDF417, Composite Symbology, QR Code
Programming Language		SBPL
<b>COMMUNICATION INTERFACE</b>		
Interface Options		RS232C, USB (2.0), LAN (10/100BaseT)
MEMORY		16 MB SDRAM, 16 MB Flash ROM, SD Card Slot
<b>OPERATING CHARACTERISTICS</b>		
Power Requirements		100-120/200-240 Volts AC + 10%, 50/60 Hertz + 5%
Environment	Operating	41° - 104°F (5° - 40°C), 15 - 85% RH, non-condensing
	Storage	-4° - 140°F (-20° - 60°C), 15 - 85% RH, non-condensing
Dimensions		8.4" W (213 mm) x 11.9" D (303 mm) x 11.1" H (281 mm)
Weight		30 lbs. (13.5 kg)
OPTIONS		Label Cutter

