

The B-FV4 powerful desktop printer

The ideal assistant for all your printing requirements

We've designed the Toshiba B-FV4 printer series to be the perfect silent office helper. Small enough to fit into the tightest of spaces with the flexibility to integrate into any environment. Stylish and sleek yet rugged and powerful, with print speeds of up to 6 ips, it handles even the most demanding printing applications with ease.

Whether direct thermal printing or using thermal ribbons, simply choose the option that suits your application.



FEATURES

- Economical, compact, stylish and rugged
- Range of interfaces as standard
- Emulation capabilities
- Ease of use and maintenance
- Low energy consumption
- Longer 300m ribbon
- Managed printer services (MPS)
- Pour tous les environnements et applications
- Fit into the tightest of spaces
- It handles even demanding printing applications with ease



The B-FV4 powerful desktop printer

The ideal assistant for all your printing requirements

	TOSHIBA B-FV4D		TOSHIBA B-FV4T	
	GS & COURIER	MODEL TS	MODEL GS	MODEL TS
CARACTÉRISTIQUES				
- Print Method	Direct thermal		Direct thermal / thermal transfer	
- Dimensions	184 (W) x 226 (D) x 166 (H) mm Label w/o Liner & Courier models: 184 (W) x 226 (D) x 199 (H) mm		220 (W) x 279 (D) x 182 (H) mm	
- Weight	1.8 kg		2.4 Kg	
- User Interface	x2 LED (colours: green, amber, red)			
- Operating Temp./Humidity	5 to 40°C (25 to 85% non-condensing RH)			
- Power Supply	AC adaptor (60W)		AC adaptor (90W)	
PRINT				
- Resolution	203dpi	300dpi	203dpi	300dpi
- Speed (max.)	Up to 152.4mm/s	Up to 101.6mm/s	Up to 152.4mm/s	Up to 101.6mm/s
- Speed (peel-off)	Up to 76.2mm/s			
- Print Width (max.)	108mm	105.7mm	108mm	105.7mm
- Print Length (max.)	995mm	453.2mm	995mm	453.2mm
- Print Length (peel-off; max.)	Up to 152.4mm continuous printing			
RIBBON				
- Width	-		40 to 110mm	
- Length	-		300m (Toshiba approved ribbon)	
MEDIA				
- Alignment	Centred			
- Media (backing paper) Width	25.4 to 118mm			
- Label Thickness	0.06 to 0.19mm			
- Media Shape	Roll-fed, fanfold, die-cut, continuous, tag stock, receipt			
- Inner Media Roll Diameter	25.4 or 38.1mm (optional: 76.2mm)			
- Outer Media Roll Diameter	Standard: 127.0mm (max.), optional: 203.2mm (max.)			
SOFTWARE & CONNECTIVITY				
- Emulations	ZPL II (EPL 2, DPL & IPL supported in future). (IPL - 203dpi only)			
- Printer Driver	Windows: 8 (32 bit/64 bit), 7 (32 bit/64 bit), Vista, XP, Server 2008 R2, Server 2008, Server 2003			
- Host Interface	Type 1: USB 2.0, LAN 10/100 Base (excl. China) Type 2: USB 2.0, LAN 10/100 Base, RS-232C (max. 115,200 bps) Type 3: USB 2.0, IEEE1284 Courier models: USB 2.0, LAN 10/100 Base, RS-232C (max. 115,200 bps)			
OPTIONS				
	Peel-off module (standard on Courier model) - full cutter module* - partial cutter module** - external 203mm OD media stand* - WLAN I/F (802.11b/g)*** or Bluetooth I/F***			

*n/a on Label w/o Liner model **n/a on Label w/o Liner & Courier models ***coming soon

Please note: the B-FV4D is still under development, as noted in the specifications listed. The specifications are subject to change without prior notice. Please contact your sales representative for the latest update.

